






















HPL05041EN

DILA, DILM

Connection type	Pole	conventional thermal current $I_{th} = I_e$ AC-1 at 60 °C Open $I_{th} = I_e$ A	Contact configuration N/O = normally open contact SF = N/O early make NC = normally closed contact ÖS = NC late-break	Circuit symbol	For use with	Part no. Article no.	Price See price list	Std. pack	Notes
Side-mounting auxiliary contacts									
	Screw terminals	1 pole	10	1 N/O	—		DILM(C)7... DILM(C)9... DILM(C)12... DILM(C)15... DILMP20... DILA(C)...	1 off 	1)
				—	1 NC				
	Spring-loaded terminals	1 pole	10	1 N/O	—		DILM17... DILM25... DILM32... DILM38...	1 off 	1)
				—	1 NC				
	Screw terminals	2 pole	10	1 N/O	1 NC		DILM17... DILM25... DILM32... DILM38...	1 off 	Can only be left on the contactor. Cannot be combined with mechanical interlock
Side-mounting auxiliary contacts									
	Screw terminals	2 pole	10	1 N/O	1 NC		DILM250 - DILH2600	1 off 	1)
			10	1 N/O	1 NC				
			10	1 SF	1 ÖS				
	Screw terminals	2 pole	10	1 N/O	1 NC		DILM40 - DILM225A DILMP63 - DILMP200	1 off 	1)
			10	1 SF	1 ÖS				
			10	1 N/O	1 NC				

Notes

- 1)
- Interlocked opposing contacts according to IEC/EN 60947-5-1 Annex L, inside the auxiliary contact module, also for the integrated auxiliary contacts of the DILM7 – DILM32 (not NO early-make and NC late-break)
 - Auxiliary NC usable as mirror contact according to IEC/EN 60947-4-1, Annex F (no NC late-breaks)
 - No auxiliary contact is possible between 2 contactors with mechanical interlock.

Information relevant for export to North America



2)

Product Standards IEC/EN 60947-4-1;
 UL 508; CSA-C22.2 No. 14-05;
 CE marking
 UL File No.E29184
 UL CCNNKCR
 CSA File No.012528
 CSA Class No.3211-03, 3211-04
 NA Certification UL Listed,
 CSA certified