



FOAM CONCENTRATES UNIROL 3 % F-15

UNIROL 3% F-15 is a Fluoroprotein foam concentrate for use on decks and in machinery spaces. It is intended for use as a 3% proportioned solution either in fresh, salt or hard water. The correct proportioning ratio is 3 parts of concentrate to 97 parts of water. UNIROL 3% F-15 is approved for marine applications according to the latest IMO Msc 1312.

Features

- Approved to Msc 1312 and UL162
- Class A+B Fires
- 10 Year shelf life
- Globally available in 20 L and 200 L

Benefits

- Approved to latest IMO regulations
- Ideal for use on Oil Tankers
- When stored correctly in accordance with the manufacturer's guidelines or in the containers it is supplied in, it will generally have a shelf life in excess of 10 years
- Global availability, latest IMO regulations, fleet flexibility and standardisation make it ideal for a long term solution to any foam concentrate requirements

UNIROL 3% 20 L AND 200 L

Technical Data

Type	Flouroprotein
Usage	Deck & Portable Applicators
Pump	Centrifugal
Density @ g/ml 20 °C	1.16 ± 0.02
Viscosity 20 °C mm ² /s	10.0 ± 4.0
Usage Temperature	-10 °C to +60 °C
pH @ 20 °C	7.0 - 0.50
Freezing Point	-15 ° C
Pour Point	<-12 °C
Sediments, Max (%Vol)	< 0.25
Expansion	Low
Expansion Ratio	7.0
Drainage In Time 25 %	5:00

Ordering Information

Product Number	Product Name
592204	UNIROL 3 % F-15 Foam Concentrate 20 L Can
556084	UNIROL 3 % F-15 Foam Concentrate 200 L Drum