

50 & 100 lb. CARBON DIOXIDE

Large volume CO₂ protection provided in either 50 or 100 lb. (2 - 50 lb. cylinders) wheeled extinguishers. Rugged construction and easy to operate with a "quick opening" 'T' handle valve and horn mounted shut-off valve. A logical choice in areas where a Class B:C non-contaminating agent is required and where hand portable extinguishers do not provide adequate protection.

FEATURES:

- Heavy Duty Steel Carriages
- Quick Opening Brass Valve
- Squeeze Grip Chrome Plated Discharge Valve
- Reinforced Wire Braided Hose and Shock Resistant Horn to Reduce Static Electricity
- Brass Hose Fittings
- Aluminum UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Pictogram Instructional Label
- DOT/TC Cylinder with Quick Opening Brass Valve
- Clean, Non-Contaminating Odorless Gas
- 5 Year Warranty



SPECIFICATIONS		CARBON DIOXIDE	
MODEL NUMBER	333	334	
AGENT TYPE	CARBON DIOXIDE		
UL & ULC RATING	20B:C		
CAPACITY (LB. / KG)	50 / 22.7	100 / 45.4	
SHIPPING WT. (LB. / KG)	257 / 116.6	461 / 209.3	
HEIGHT (IN. / CM)	47 / 119.5		
WIDTH (IN. / CM)	23 / 58.4		
DEPTH (IN. / CM)	48 / 122		
DISCHARGE TIME (SEC.)	44+-5	74 +-8	
DISCHARGE RANGE (FT. / M)	10 - 15 / 3.04 - 4.57		
OPERATING TEMP. (F / C)	-22° to +120° / -30° to +49°		
HOSE LENGTH (FT. / M)	40 / 12.1		
HOSE DIAMETER (IN. / CM)	.25 / .635		
WHEELS [FULL PNEUMATIC] (IN. / CM)	16 X 4 / 40.64 X 10.16		
USCG APPROVED	YES		

Available Options:

- 100 lb. Stationary Design - Model 335
- Semi-Pneumatic Wheels

Test Standards:

CAN/ULC S503 & ANSI/UL 154
CAN/ULC S508 & ANSI/UL 711

DESIGNED AND ASSEMBLED IN USA